



TorChuck

CONSTRUCTION MACHINERY



10Q



12K



18K Pro



16C

小型挖掘机 06Q SMALL EXCAVATOR 06Q



产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

众诚发动机/进口油缸、油管内置NOK密封圈/双齿轮泵/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座

椅/标准挖斗/标准顶棚

ZHONGCHENG engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/twin gear pump/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, - municipal projects, break concrete, dredging river and other working environment.

型号	06Q
重量	
工作重量	660kg
尺寸	
运输长度	2287mm
运输宽度	700mm
运输高度	1684mm
最大挖掘半径	2354mm
最大挖掘深度	1200mm
最大挖掘高度	2214mm
最大卸载高度	1486mm
最大挖掘力	7.2KN
驱动	
发动机品牌	众诚
发动机型号	TR306
最大功率	6.3KW
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	06Q
WEIGHT	
Operating weight	660kg
SIZE	
Total length	2287mm
Total width	700mm
Total height	1684mm
Max. digging radius	2354mm
Max. digging depth	1200mm
Max. digging height	2214mm
Counterweight ground clearance	1486mm
Max. digging force	7.2KN
DRIVE	
Engine brand	ZONGCHENG
Engine model	TR306
Maximum power	6.3KW
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 10Q

SMALL EXCAVATOR 10Q



变量柱塞泵
Variable piston pump



后翻式座椅
Rear-tilting seat



操作简单
Easy operation



内置油管
Built-in oil pipe

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

百利通/科普发动机/进口油缸、油管内置NOK密封圈/柱塞泵/后掀式座椅/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚

Briggs & Stratton/KOOP engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/plunger pump/Rear-tilting seat/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	10Q
重量	
工作重量	1000kg
尺寸	
运输长度	2890mm
运输宽度	930mm
运输高度	2190mm
最大挖掘半径	3163mm
最大挖掘深度	1835mm
最大挖掘高度	2800mm
最大卸载高度	1945mm
最大挖掘力	7.2KN
驱动	
发动机品牌	百利通/科普
发动机型号	XR13.5/192F
最大功率	13.5HP/10HP
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	10Q
WEIGHT	
Operating weight	1000kg
SIZE	
Total length	2890mm
Total width	930mm
Total height	2190mm
Max. digging radius	3163mm
Max. digging depth	1835mm
Max. digging height	2800mm
Counterweight ground clearance	1945mm
Max. digging force	7.2KN
DRIVE	
Engine brand	R&S/KOOP
Engine model	XR13.5/192F
Maximum power	13.5HP/10HP
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 12Q

SMALL EXCAVATOR



EPA



坐落式安全锁
Mounted Safety Lock



LED液晶显示器
LED LCD



脚踏式破碎
Foot-operated Crusher



可加装钢履带
Steel tracks can be installed.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

科普192发动机/进口油缸、油管内置NOK密封圈/双齿轮泵/可调节推土铲/耐磨工程橡胶履带/可调节驾驶室座椅/标准挖斗/标准顶棚
KOOP192F engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/twin gear pump/-adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, -municipal projects, break concrete, dredging river and other working environment.

型号	12Q
重量	
工作重量	1250kg
尺寸	
运输长度	2981mm
运输宽度	930-1105mm
运输高度	2287mm
最大挖掘半径	3057mm
最大挖掘深度	1717mm
最大挖掘高度	2717mm
最大卸载高度	1866mm
最大挖掘力	9KN
驱动	
发动机品牌	科普/百利通
发动机型号	192F/XR13.5
最大功率	10HP/13.5HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	12Q
WEIGHT	
Operating weight	1250kg
SIZE	
Total length	2981mm
Total width	930-1105mm
Total height	2287mm
Max. digging radius	3057mm
Max. digging depth	1717mm
Max. digging height	2717mm
Counterweight ground clearance	1866mm
Max. digging force	9KN
DRIVE	
Engine brand	KOOP/B&S
Engine model	192F/XR13.5
Maximum power	10HP/13.5HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 12K SMALL EXCAVATOR 12K



油管内置
Built-in Hydraulic Oil Line

工程橡胶履带
Engineering rubber tracks



操作简单
Easy operation

可加装钢履带，驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

百利通/科普发动机/进口油缸、油管内置NOK密封圈/可开式后门/可调节推土铲/耐磨工程橡胶履带/可调节驾驶座椅/标准挖斗/标准顶棚

Briggs & Stratton/KOOP engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/openable rear door/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	12K
重量	
工作重量	1000kg
尺寸	
运输长度	2200mm
运输宽度	930mm
运输高度	2200mm
最大挖掘半径	2400mm
最大挖掘深度	1650mm
最大挖掘高度	2550mm
最大卸载高度	1850mm
最大挖掘力	7.2KN
驱动	
发动机品牌	百利通/科普
发动机型号	XR13.5/192F
最大功率	13.5HP/10HP
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	12K
WEIGHT	
Operating weight	1000kg
SIZE	
Total length	2200mm
Total width	930mm
Total height	2200mm
Max. digging radius	2400mm
Max. digging depth	1650mm
Max. digging height	2550mm
Counterweight ground clearance	1850mm
Max. digging force	7.2KN
DRIVE	
Engine brand	B&S/KOOP
Engine model	XR13.5/192F
Maximum power	13.5HP/10HP
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 12K Pro

SMALL EXCAVATOR



两侧先导操作
Pilot operation on both sides



工程橡胶履带
Engineering rubber tracks



大臂侧摆
Big arm side swing

可加装钢履带，驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

百利通/科普发动机/进口油缸、油管内置NOK密封圈/液压先导操作/前翻式座椅/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚
Briggs & Stratton/KOOP engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Pilot control handle/forward flip-up seat/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, - municipal projects, break concrete, dredging river and other working environment.

型号	12K Pro
重量	
工作重量	1050kg
尺寸	
运输长度	2200mm
运输宽度	930mm
运输高度	2200mm
最大挖掘半径	2400mm
最大挖掘深度	1650mm
最大挖掘高度	2550mm
最大卸载高度	1850mm
最大挖掘力	7.2KN
驱动	
发动机品牌	百利通/科普
发动机型号	XR13.5/192F
最大功率	13.5HP/10HP
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	12K Pro
WEIGHT	
Operating weight	1050kg
SIZE	
Total length	2200mm
Total width	930mm
Total height	2200mm
Max. digging radius	2400mm
Max. digging depth	1650mm
Max. digging height	2550mm
Counterweight ground clearance	1850mm
Max. digging force	7.2KN
DRIVE	
Engine brand	B&S/KOOP
Engine model	XR13.5/192F
Maximum power	13.5HP/10HP
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 13K

SMALL EXCAVATOR



前翻式座椅
Flip-forward seat



工程橡胶履带
Engineering rubber tracks



操作简单
Easy operation

可加装钢履带，驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

百利通/科普发动机/进口油缸、油管内置NOK密封圈/前翻式座椅/可调节推土铲/耐磨工程橡胶履带/可调节式驾驶座椅/标准挖斗/标准顶棚

Briggs & Stratton/KOOP engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/forward flip-up seat/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	13K
重量	
工作重量	1100kg
尺寸	
运输长度	2200mm
运输宽度	1100mm
运输高度	2200mm
最大挖掘半径	3100mm
最大挖掘深度	1740mm
最大挖掘高度	2550mm
最大卸载高度	1710mm
最大挖掘力	11KN
驱动	
发动机品牌	百利通/科普
发动机型号	XR13.5/192F
最大功率	13.5HP/10HP
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	13K
WEIGHT	
Operating weight	1100kg
SIZE	
Total length	2200mm
Total width	1100mm
Total height	2200mm
Max. digging radius	3100mm
Max. digging depth	1740mm
Max. digging height	2550mm
Counterweight ground clearance	1710mm
Max. digging force	11KN
DRIVE	
Engine brand	B&S/KOOP
Engine model	XR13.5/192F
Maximum power	13.5HP/10HP
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 13K Pro

SMALL EXCAVATOR



前翻式座椅
Flip-forward seat



备用油管+截止阀
Spare Oil Pipe and
Cut-off Valve



液压先导操作
Hydraulic pilot operation

可加装钢履带，驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

百利通/科普发动机/进口油缸、油管内置NOK密封圈/液压先导操作/前翻式座椅/可调节推土铲/耐磨工程

橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚

Briggs & Stratton/KOOP engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Hydraulic pilot operation/forward flip-up seat/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	13K Pro
重量	
工作重量	1100kg
尺寸	
运输长度	2200mm
运输宽度	1100mm
运输高度	2200mm
最大挖掘半径	3100mm
最大挖掘深度	1740mm
最大挖掘高度	2550mm
最大卸载高度	1710mm
最大挖掘力	11KN
驱动	
发动机品牌	百利通/科普
发动机型号	XR13.5/192F
最大功率	13.5HP/10HP
行走特性	
行走速度	0-4km/h
爬坡能力	30°

MODEL	13K Pro
WEIGHT	
Operating weight	1100kg
SIZE	
Total length	2200mm
Total width	1100mm
Total height	2200mm
Max. digging radius	3100mm
Max. digging depth	1740mm
Max. digging height	2550mm
Counterweight ground clearance	1710mm
Max. digging force	11KN
DRIVE	
Engine brand	B&S/KOOP
Engine model	XR13.5/192F
Maximum power	13.5HP/10HP
WALKING CHARACTERISTICS	
Walking speed	0-4km/h
Climbing angle	30°

小型挖掘机 16C SMALL EXCAVATOR 16C



大臂侧摆
Boom lateral swing

液压先导操作
Hydraulic pilot handle



LED液晶显示器
LED LCD



底盘伸缩
Telescopic Undercarriage

可加装钢履带
Steel tracks can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

久保田D722发动机/进口油缸、油管内置NOK密封圈/大臂侧摆/底盘伸缩/高低速/柱塞泵/前翻式座椅/液压先导手柄/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚
Kubota D722 engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Boom Swing/Telescopic Chassis/High-Low Speed/plunger pump/Forward flip-up seat/Hydraulic pilot handle/-adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。
Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, -municipal projects, break concrete, dredging river and other working environment.

型号	16C
重量	
工作重量	1500kg
尺寸	
运输长度	2400mm
运输宽度	1100mm-1400mm
运输高度	2200mm
最大挖掘半径	3450mm
最大挖掘深度	2050mm
最大挖掘高度	3020mm
最大卸载高度	2140mm
最大挖掘力	15KN
驱动	
发动机品牌	久保田
发动机型号	D722
最大功率	14HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	16C
WEIGHT	
Operating weight	1500kg
SIZE	
Total length	2400mm
Total width	1100mm-1400mm
Total height	2200mm
Max. digging radius	3450mm
Max. digging depth	2050mm
Max. digging height	3020mm
Counterweight ground clearance	2140mm
Max. digging force	15KN
DRIVE	
Engine brand	Kubota
Engine model	D722
Maximum power	14HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 17Q

SMALL EXCAVATOR



变量柱塞泵
Variable piston pump



可掀式发动机舱
Rear-tilting seat



LED液晶显示器
LED LCD



大臂油缸上置油缸
Top-mounted Boom Cylinder

可加装钢履带
Steel tracks can be installed.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

莱动385B/进口油缸、油管内置NOK密封圈/后掀式发动机机舱/泰丰变量柱塞泵/泰丰多路阀/可调节推土铲/

耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚

LAIDONG KM385B engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Hinged Engine Compartment Hood/Taifeng Variable Displacement Piston Pump / Taifeng Multi-way Valve/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	17Q
重量	
工作重量	1500kg
尺寸	
运输长度	3260mm
运输宽度	1100mm
运输高度	2400mm
最大挖掘半径	3448mm
最大挖掘深度	1880mm
最大挖掘高度	2910mm
最大卸载高度	2150mm
最大挖掘力	10KN
驱动	
发动机品牌	莱动
发动机型号	KM385B
最大功率	24HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	17Q
WEIGHT	
Operating weight	1500kg
SIZE	
Total length	3260mm
Total width	1100mm
Total height	2400mm
Max. digging radius	3448mm
Max. digging depth	1880mm
Max. digging height	2910mm
Counterweight ground clearance	2150mm
Max. digging force	10KN
DRIVE	
Engine brand	LAIDONG
Engine model	KM385B
Maximum power	24HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 18K SMALL EXCAVATOR 18K



久保田发动机
Kubota D722

液压先导操作
Hydraulic pilot handle



显示仪表
Display instrument

可加装钢履带, 驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活, 便于小地形、空间狭窄作业;
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷, 运输方便;
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材, 运用喷塑工艺处理, 防锈防腐;
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机, 运行平稳, 可靠性高;
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转, 灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

久保田D722发动机/进口油缸、油管内置NOK密封圈/双齿轮泵/前翻式座椅/液压先导手柄/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚
Kubota D722 engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Dual Gear Pump/Forward flip-up seat/Hydraulic pilot handle/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, -municipal projects, break concrete, dredging river and other working environment.

型号	18K
重量	
工作重量	1400kg
尺寸	
运输长度	2200mm
运输宽度	1100mm
运输高度	2200mm
最大挖掘半径	3280mm
最大挖掘深度	1910mm
最大挖掘高度	2660mm
最大卸载高度	1900mm
最大挖掘力	15KN
驱动	
发动机品牌	久保田
发动机型号	D722
最大功率	14HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	18K
WEIGHT	
Operating weight	1400kg
SIZE	
Total length	2200mm
Total width	1100mm
Total height	2200mm
Max. digging radius	3280mm
Max. digging depth	1910mm
Max. digging height	2660mm
Counterweight ground clearance	1900mm
Max. digging force	15KN
DRIVE	
Engine brand	Kubota
Engine model	D722
Maximum power	14HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 18Q SMALL EXCAVATOR 18Q



坐落式安全锁
Mounted Safety Lock



LED液晶显示器
LED LCD



脚踏式破碎
Foot-operated Crusher



可加装钢履带
Steel tracks can be installed.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

莱动385B/进口油缸、油管内置NOK密封圈/双齿轮泵/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/

标准挖斗/标准顶棚

LAIDONG KM385B engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/twin gear pump/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	18Q
重量	
工作重量	1500kg
尺寸	
运输长度	3249mm
运输宽度	1120mm
运输高度	2314mm
最大挖掘半径	3496mm
最大挖掘深度	2091mm
最大挖掘高度	3028mm
最大卸载高度	2190mm
最大挖掘力	10KN
驱动	
发动机品牌	莱动/久保田
发动机型号	KM385B/D722
最大功率	24HP/13.9HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	18Q
WEIGHT	
Operating weight	1500kg
SIZE	
Total length	3249mm
Total width	1120mm
Total height	2314mm
Max. digging radius	3496mm
Max. digging depth	2091mm
Max. digging height	3028mm
Counterweight ground clearance	2190mm
Max. digging force	10KN
DRIVE	
Engine brand	LAIDONG/KUBOTA
Engine model	KM385B/D722
Maximum power	24HP/13.9HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 18K Pro

SMALL EXCAVATOR



230mm加宽履带
Engineering rubber tracks



两侧先导操作
Pilot operation on both sides



变量柱塞泵
Variable piston pump

久保田D722
Kubota D722



可加装钢履带，驾驶室
Steel tracks and cab can be added.

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

久保田D722发动机/进口油缸、油管内置NOK密封圈/柱塞泵/前翻式座椅/液压先导手柄/可调节推土铲/耐

磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚

Kubota D722 engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/plunger pump/- Forward flip-up seat/Hydraulic pilot handle/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, - municipal projects, break concrete, dredging river and other working environment.

型号	18K Pro
重量	
工作重量	1500kg
尺寸	
运输长度	2200mm
运输宽度	1100mm
运输高度	2200mm
最大挖掘半径	3280mm
最大挖掘深度	1910mm
最大挖掘高度	2660mm
最大卸载高度	1900mm
最大挖掘力	15KN
驱动	
发动机品牌	久保田
发动机型号	D722
最大功率	14HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	18K Pro
WEIGHT	
Operating weight	1500kg
SIZE	
Total length	2200mm
Total width	1100mm
Total height	2200mm
Max. digging radius	3280mm
Max. digging depth	1910mm
Max. digging height	2660mm
Counterweight ground clearance	1900mm
Max. digging force	15KN
DRIVE	
Engine brand	Kubota
Engine model	D722
Maximum power	14HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 20C

SMALL EXCAVATOR 20C



高低速
High/Low Speed

两侧先导操作
Pilot operation on both sides



大臂油缸上置
Top-mounted Boom Cylinder



两侧先导操作
Pilot operation on both sides



产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

莱动385B发动机/进口油缸、油管内置NOK密封圈/大臂侧摆/高低速/柱塞泵/前翻式座椅/液压先导手柄/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚
LAIDONG KM385B engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Boom Swing/High-Low Speed/plunger pump/Forward flip-up seat/Hydraulic pilot handle/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, municipal projects, break concrete, dredging river and other working environment.

型号	20C
重量	
工作重量	1850kg
尺寸	
运输长度	2400mm
运输宽度	1250mm
运输高度	2200mm
最大挖掘半径	3450mm
最大挖掘深度	2050mm
最大挖掘高度	3020mm
最大卸载高度	2140mm
最大挖掘力	15KN
驱动	
发动机品牌	莱动
发动机型号	KM385B
最大功率	15HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	20C
WEIGHT	
Operating weight	1850kg
SIZE	
Total length	2400mm
Total width	1250mm
Total height	2200mm
Max. digging radius	3450mm
Max. digging depth	2050mm
Max. digging height	3020mm
Counterweight ground clearance	2140mm
Max. digging force	15KN
DRIVE	
Engine brand	LAIDONG
Engine model	KM385B
Maximum power	15HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°

小型挖掘机 22C

SMALL EXCAVATOR 22C



高低速
High/Low speed

三面可开
Three-Sided Access



大臂侧摆
Boom Swing



力士乐变量柱塞泵
Bosch Rexroth Axial
Piston Pump



产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活，便于小地形、空间狭窄作业；
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷，运输方便；
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材，运用喷塑工艺处理，防锈防腐；
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机，运行平稳，可靠性高；
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转，灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置/STANDARD CONFIGURATION

洋马发动机/进口油缸、油管内置NOK密封圈/大臂侧摆/高低速/力士乐柱塞泵/前翻式座椅/液压先导手柄/可调节推土铲/耐磨工程钢履带/可调式驾驶座椅/标准挖斗
Yanmar 3TNV80 engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/Boom swing/High-low speed/Bosch Rexroth axial piston pump/Forward flip-up seat/Hydraulic pilot handle /Adjustable bulldozer/Wear-resistant engineering steel track/ Adjustable driving seat/Standard bucket

选装配置/OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗
Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, - municipal projects, break concrete, dredging river and other working environment.

型号	22C
重量	
工作重量	2100kg
尺寸	
运输长度	3550mm
运输宽度	1100mm-1400mm
运输高度	2200mm
最大挖掘半径	3800mm
最大挖掘深度	2050mm
最大挖掘高度	3155mm
最大卸载高度	2133mm
最大挖掘力	15KN
驱动	
发动机品牌	洋马
发动机型号	3TNV80
最大功率	20HP
行走特性	
行走速度	0-8km/h
爬坡能力	30°

MODEL	22C
WEIGHT	
Operating weight	2100kg
SIZE	
Total length	3550mm
Total width	1100mm-1400mm
Total height	2200mm
Max. digging radius	3800mm
Max. digging depth	2050mm
Max. digging height	3155mm
Counterweight ground clearance	2133mm
Max. digging force	15KN
DRIVE	
Engine brand	Yanmar
Engine model	3TNV80
Maximum power	20HP
WALKING CHARACTERISTICS	
Walking speed	0-8km/h
Climbing angle	30°

小型挖掘机 25K

SMALL EXCAVATOR 25K



大臂油缸上置
Top-mounted Boom Cylinder



一键启动
Pilot operation on both sides



大臂侧摆
Boom lateral swing



底盘伸缩
Telescopic chassis

可加装钢履带, 驾驶室
Steel tracks and cab can be added

产品用途 PRODUCT APPLICATION

运用于路面修复、混凝土破碎、埋设电缆、自来水管道的铺设、园林栽培及河道河沟清淤工程、建筑工程等各种作业环境。具备挖掘、破碎、清沟、钻孔、推土等多功能。

It is used to restore the ground, break the concrete, and for cable casting, water pipe laying, planting, cleaning of river/ditch and construction project. It has several functions: excavation, breaking, ditch cleaning, drilling, bulldozing and ect.

性能特点 FEATURE

- ◆小巧灵活, 便于小地形、空间狭窄作业;
Compact and flexible, convenient for small terrain and narrow space operations.
- ◆操作简单便捷, 运输方便;
Simple and convenient operation, convenient transportation.
- ◆采用优质加厚钢材, 运用喷塑工艺处理, 防锈防腐;
Use thicker high-quality steel, apply plastic molding process, prevent rust and anti-corrosion.
- ◆采用国际知名品牌减速机, 运行平稳, 可靠性高;
The use of internationally renowned brand reducers provides smooth operation and high reliability.
- ◆360度车身自由旋转, 灵动机身为用户户外工作带来便利。
The 360-degree body rotates freely, and the smart body facilitates outdoor work.

标准配置 / STANDARD CONFIGURATION

莱动385B/珀金斯/洋马3tnv80发动机/进口油缸、油管内置NOK密封圈/柱塞泵/前翻式座椅/液压先导手柄

/可调节推土铲/耐磨工程橡胶履带/可调式驾驶座椅/标准挖斗/标准顶棚

Laidong 385B/Perkins/Yanmar 3TNV80 engine/Imported oil cylinders and oil pipes with built-in NOK sealing ring/plunger pump/Forward flip-upseat/Hydraulic pilot handle/adjustable bulldozer/wear-resistant engineering rubber track/ Adjustable driving seat/standard bucket

选装配置 / OPTIONAL CONFIGURATION

破碎锤/松土器/抓木器/耙子/旋挖钻/大挖斗/泥浆斗

Hammer / Ripper / Log grapple / Rake / Auger drill / Large bucket / Mud bucket

适用范围 APPLICATION

适合于室内拆除、旱厕改造、工程破拆、开荒山、小型土石方工程、市政工程、混凝土破碎、河道清淤等作业环境。Applicable to indoor demolition, toilet upgrading, engineering forcible entry, excavate barren hills, small earthwork, - municipal projects, break concrete, dredging river and other working environment.

型号	25K
重量	
工作重量	2000kg
尺寸	
运输长度	3700mm
运输宽度	1100mm-1400mm
运输高度	2200mm
最大挖掘半径	3800mm
最大挖掘深度	2241mm
最大挖掘高度	3200mm
最大卸载高度	2290mm
最大挖掘力	16KN
驱动	
发动机品牌	莱动/珀金斯/洋马
发动机型号	KM385/403D-11/3TNV80
最大功率	25HP/24HP/24HP
行走特性	
行走速度	0-6km/h
爬坡能力	30°

MODEL	25K
WEIGHT	
Operating weight	2000kg
SIZE	
Total length	3700mm
Total width	1100mm-1400mm
Total height	2200mm
Max. digging radius	3800mm
Max. digging depth	2241mm
Max. digging height	3200mm
Counterweight ground clearance	2290mm
Max. digging force	16KN
DRIVE	
Engine brand	Laidong/Perkins/Yanmar
Engine model	KM385/403D-11/3TNV80
Maximum power	25HP/24HP/24HP
WALKING CHARACTERISTICS	
Walking speed	0-6km/h
Climbing angle	30°